

Project Ref:


COLOURBOX.STUDIO

Item Ref:


APT2 Apollo Plaster-In Tilt Twin

2x75mm Adjustable Architectural Downlight

Spectrum




Cut Out: Ø2x95mm
Visible Diameter: Ø2x75mm



Luminaire Details

Type	Twin Adjustable Architectural Downlight
Light Source	Spectrum Pure LED Light Engine Spectrum Ambient LED Light Engine
IP Rating	IP54 (Bathroom Zones 1&2)
Fire Rating	Optional with Envirograf accessory see page 2
Warranty	Five Years
Class	SELV Class III
Construction	Machined steel and aluminium
Bezel Finish	White RAL9010 fine texture
Bezel Options	Black, Bronze, Copper RAL finish to order
Baffle Finish	Black RAL9005
Baffle Options	White RAL9010, Bronze, Copper RAL finish to order



Dimensions

Cut Out	Ø2x95mm
Visible Diameter	Ø2x75mm
Skim Plate Width	145mm
Skim Plate Length	255mm
Hole Saw	Starrett FCH0334
Clearance	10mm above 50mm from edge of cut out

Installation Notes

Do NOT cover with insulation.
Plaster-in installation.
Please ensure installer is familiar with this method.

Light Engine Details

Spectrum Pure

LED	Bridgelux Thrive
Power	12.4w
Engine Lumens	1200lm
Colour Temp	2700K 3000K 4000K
Optic	15° 24° 38° 60° Beam
CRI	Ra98 (R9: 99)
Rated Life	tp90° >50,000hrs L90B10

Spectrum Ambient

LED	Bridgelux Vesta
Power	12.4w
Engine Lumens	1200lm
Colour Temp	Warm Dim 1800-3000K
Optic	15° 24° 38° 60° Beam
CRI	Ra97 (R9: 99)
Rated Life	tp90° >50,000hrs L90B10

Driver Details

Mains Dim	Osram OTe13 350mA 35v Remote mounted Pre-wired with 0.35m LS0H mains cable
DALI	350mA 35v Remote mounted
Casambi	350mA 35v Remote mounted

NB: To check current dimming compatibility contact us at info@colourbox.studio.

Colourbox Studio Ltd

52 St Mary's Road Faversham Kent ME13 8EH
Tel: 01795 505370 Email: info@colourbox.studio


www.colourbox.studio

APT2 Apollo Plaster-In Tilt Twin

2x75mm Adjustable Architectural Downlight

Spectrum

Beam Diagrams



Fire Rating Accessory


F Fire Collar IDR53117
Manufacturer Envirograf
Technology Intumescent 60mins
Installation Factory fitted. Can be retro-fitted.

Optical Accessories

HCL Honeycomb Louvre
BSL Beam Softening Lens
OSL Opal Spreader Lens
CWF Colour Warming Filter

Electrical Accessory

CF Click Flow Plug/Play Connector



Product Configurator

Bezel			Light Engine			Driver		Accessories	
Bezel	Bezel Colour	Baffle Colour	Light Engine	Beam	Colour Temperature	OM	Osram Mains Dim	F	Fire Collar
W (RAL9010)	BB (RAL9005)	WB (RAL9010)	Pure PUR	15°	927 (2700K)	D	DALI	CF	Click Flow Connector
B (RAL9005)	CB (Copper)	CB (Copper)	Ambient AMB	24°	930 (3000K)	TC	Tridonic Casambi	HCL	Honeycomb Louvre
C (Copper)	BZ (Bronze)	BZB (Bronze)		38°	940 (4000K)			BSL	Beam Softening Lens
BZ (Bronze)	RAL (RAL)	RAL (RAL)		60°	1830 (1800-3000K)			EMG	3hr Emergency Conversion
Example:	APT2.W.BB/		PUR.38.927/			OM/		F/BSL	